

Information User instruction

Safety gloves against mechanical risks

Manufacturer

UVEX SAFETY Gloves GmbH & Co. KG
Elso-Klöver-Str. 6, 21337 Lüneburg
Postfach 24 47 · 21314 Lüneburg
GERMANY

Tel.: +49 4131 9502-0
Fax: +49 4131 84338
Email: gloves@uvex.de
Website: uvex-safety.de

Type uvex phynomic C5

Basic glove material Dyneema®Diamond Technology, polyamide, elasthan

Coating material

Aqua-polymer foam coating
100 Pairs

Smallest packing unit

Available sizes 6, 7, 8, 9, 10, 11, 12


Pictogram and performance levels

EN 388 : 2003



4 X 4 2

Performance levels



Puncture resistance

Tear resistance

Cut resistance

Abrasion resistance

Pictogram and performance levels according to EN 388:2003 (highest performance level: 4/cut resistance: 5)

All levels only apply to the coated areas of the glove.

The overall classification of gloves with two or more unconnected layers does not necessarily denote the performance level of the outer layer.

EC notified body

CTC - Centre Technique Cuir Chaussure Maroquinerie
4. rue Hermann Frenkel · 69367 Lyon Cedex 07 · France
No.: 0075

Cleaning

No cleaning or care recommended

Storage

Store in a dark, dry place.

Handling

New and used gloves should be thoroughly checked. Particularly after cleaning, ensure that they are not damaged (e.g. incisions, holes).

Disposal

The gloves should be disposed of properly as household waste. If they come into contact with chemicals, please consult the chemical manufacturer's waste disposal guidelines.

Warning

Gloves should not be worn where there is a risk of being caught in moving machinery parts.