

Information User instruction

Safety gloves against chemical and mechanical risks

Manufacturer

UVEX SAFETY Gloves GmbH & Co. KG Elso-Klöver-Str. 6, 21337 Lüneburg Postfach 24 47 · 21314 Lüneburg

GERMANY

uvex rubiflex S - NB80SZ **Type**

Basic glove material cotton interlock

Available sizes 9, 10, 11 Coating material

Website: uvex-safety.de

Tel.:

Fax:

Email:

Special NBR (nitrile butadiene

rubber)

20 Pairs Smallest packing unit

+49 4131 9502-0

+49 4131 84338

gloves@uvex.de

Pictogram and performance levels

EN 374: 2003 EN 388: 2003

î (**f**

Performance levels

Performance level

Pictogram and performance levels according to EN 374:2003 (lowest performance level: 1/highest performance: 6)

The sampling for penetration testing is made by general inspection level according to DIN 2859, part 1 with AQL 4.0.

Please note: The actual period of protection on the job is affected by many factors (temperature, abrasion, etc.) and can therefore differ from the performance level!

Pictogram and performance levels according to EN 388:2003 (highest performance level: 4/cut resistance: 5)

All levels only apply to the coated areas of the glove.

The noticeable difference in wearer comfort: combination of high sensitivity and tactile feel, lightness. The uvex phynomic airLite C ESD is certified according to the DIN EN 16350:2014 (1149-2) standard and is also tested based on the DIN EN 1149-1. Therefore it is perfectly applicable in ESD areas and

EC notified body TÜV Rheinland LGA Products GmbH

Tillystraße 2 · 90431 Nürnberg

No.: 0197

Cleaning only possible when not working with aggressive chemicals. Carefully rinse gloves under Cleaning

lukewarm running water.

Storage Store in a dark, dry place.

Thoroughly check before use for damage. Defective gloves should not be used. All technical data refers Handling

to the state of the gloves at delivery, unused, not stretched and at ambient temperature (EN 374).

Gloves must be disposed of when the permeation time expires.

After contamination, a change of performance cannot be excluded.

We are not aware of any substances in this product that could cause an allergic reaction.

The gloves should be disposed of properly as household waste. If they come into contact with chemicals, **Disposal**

please consult the chemical manufacturer's waste disposal guidelines.

Warning Gloves should not be worn where there is a risk of being caught in moving machinery parts.

protecting people