

Information User instruction

Safety gloves against mechanical risks

Manufacturer

UVEX SAFETY Gloves GmbH & Co. KG Elso-Klöver-Str. 6, 21337 Lüneburg Postfach 24 47 · 21314 Lüneburg GERMANY

Typeuvex C500Basic glove materialbamboo-rayon/HPPE/glass/polyamideAvailable sizes7, 8, 9, 10, 11

 Tel.:
 +49 4131 9502-0

 Fax:
 +49 4131 84338

 Email:
 gloves@uvex.de

 Website:
 uvex-safety.de

Coating material Smallest packing unit without 100 Pairs

Pictogram and performance levels

EN 388 : 2003

[i] (E

2 5 4 X Performance levels

Puncture resistance

Tear resistance

Cut resistance

Abrasion resistance

Pictogram and performance levels according to EN 388:2003 (highest performance level: 4/cut resistance: 5)

All levels only apply to the coated areas of the glove.

The overall classification of gloves with two or more unconnected layers does not necessarily denote the performance level of the outer layer.

EC notified body	TÜV Rheinland LGA Products GmbH Tillystraße 2 · 90431 Nürnberg No.: 0197
Cleaning	No cleaning or care recommended
Storage	Store in a dark, dry place.
Handling	New and used gloves should be thoroughly checked. Particularly after cleaning, ensure that they are not damaged (e.g. incisions, holes).

	We are not aware of any substances in this product that could cause an allergic reaction.
Disposal	The gloves should be disposed of properly as household waste. If they come into contact with chemicals, please consult the chemical manufacturer's waste disposal guidelines.
Warning	Gloves should not be worn where there is a risk of being caught in moving machinery parts.

protecting people