

Information User instruction

Safety gloves against mechanical risks

Manufacturer

UVEX SAFETY Gloves GmbH & Co. KG Elso-Klöver-Str. 6, 21337 Lüneburg Postfach 24 47 · 21314 Lüneburg GERMANY

Type uvex unidur - 6659 foam Basic glove material HPPE, glass, polyamide

Available sizes 6, 7, 8, 9, 10, 11

Fax: +49 4131 84338 Email: gloves@uvex.de Website: uvex-safety.de

+49 4131 9502-0

Tel.:

Coating material NBR foam coating

Smallest packing unit 200 Pairs

Pictogram and performance levels

EN 388: 2003

□i (€

Performance levels

Pictogram and performance levels according to EN 388:2003 (highest performance level: 4/cut resistance: 5)

All levels only apply to the coated areas of the glove.

The overall classification of gloves with two or more unconnected layers does not necessarily denote the performance level of the outer layer.

EC notified body SGS United Kingdom Ltd., Systems & Services Certification

202 B Worle Parkway · BS22 6WA Weston-Super-Mare, United Kingdom

No.: 0120

Cleaning No cleaning or care recommended

Storage Store in a dark, dry place.

Handling New and used gloves should be thoroughly checked. Particularly after cleaning, ensure that they are not

damaged (e.g. incisions, holes).

We are not aware of any substances in this product that could cause an allergic reaction.

DisposalThe gloves should be disposed of properly as household waste. If they come into contact with chemicals,

please consult the chemical manufacturer's waste disposal guidelines.

Warning Gloves should not be worn where there is a risk of being caught in moving machinery parts.