

## Information User instruction

## Safety gloves against chemical and mechanical risks

## Manufacturer

UVEX SAFETY Gloves GmbH & Co. KG Elso-Klöver-Str. 6, 21337 Lüneburg Postfach 24 47 · 21314 Lüneburg GERMANY

uvex profaviton - BV-06 Type Basic glove material unsupported Available sizes 8, 9, 10, 11

Tel.: +49 4131 9502-0 +49 4131 84338 Fax: gloves@uvex.de Email: Website: uvex-safety.de

**Coating material** 

Smallest packing unit


bromobutyl with Viton® coating 1 Pair

**Pictogram and performance levels** EN 374 : 2003

EN 388 : 2003



Performance level



Pictogram and performance levels according to EN 374:2003 (lowest performance level: 1/highest performance: 6)

The sampling for penetration testing is made by general inspection level according to DIN 2859, part 1 with AQL 4.0.

Please note: The actual period of protection on the job is affected by many factors (temperature, abrasion, etc.) and can therefore differ from the performance level!

Pictogram and performance levels according to EN 388:2003 (highest performance level: 4/cut resistance: 5)

All levels only apply to the coated areas of the glove.

The noticeable difference in wearer comfort: combination of high sensitivity and tactile feel, lightness. The uvex phynomic airLite C ESD is certified according to the DIN EN 16350:2014 (1149-2) standard and is also tested based on the DIN EN 1149-1. Therefore it is perfectly applicable in ESD areas and

EC notified body	Institut für Arbeitsschutz der Deutschen Gesetzlichen Unfallversicherung Alte Heerstraße 111 · 53757 Sankt Augustin No.: 0121
Cleaning	Cleaning only possible when not working with aggressive chemicals. Carefully rinse gloves under lukewarm running water.
Storage	Store in a dark, dry place.
Handling	Thoroughly check before use for damage. Defective gloves should not be used. All technical data refers to the state of the gloves at delivery, unused, not stretched and at ambient temperature (EN 374). Gloves must be disposed of when the permeation time expires.
	After contamination, a change of performance cannot be excluded. We are not aware of any substances in this product that could cause an allergic reaction.
Disposal	The gloves should be disposed of properly as household waste. If they come into contact with chemicals, please consult the chemical manufacturer's waste disposal guidelines.
Warning	Gloves should not be worn where there is a risk of being caught in moving machinery parts.

## protecting people