

## Information User instruction

### Safety gloves against chemical and mechanical risks

#### Manufacturer

UVEX SAFETY Gloves GmbH & Co. KG  
Elso-Klöver-Str. 6, 21337 Lüneburg  
Postfach 24 47 · 21314 Lüneburg  
GERMANY

Tel.: +49 4131 9502-0  
Fax: +49 4131 84338  
Email: gloves@uvex.de  
Website: uvex-safety.de

**Type** uvex rubiflex S - NB27S  
**Basic glove material** cotton interlock  
**Available sizes** 8, 9, 10, 11

**Coating material** Special NBR (nitrile butadiene rubber)  
**Smallest packing unit** 80 Pairs

#### Pictogram and performance levels


EN 374 : 2003

EN 388 : 2003

#### Performance level



#### Performance levels



Pictogram and performance levels according to EN 374:2003 (lowest performance level: 1/highest performance: 6)

The sampling for penetration testing is made by general inspection level according to DIN 2859, part 1 with AQL 4.0.

**Please note:** The actual period of protection on the job is affected by many factors (temperature, abrasion, etc.) and can therefore differ from the performance level!

Pictogram and performance levels according to EN 388:2003 (highest performance level: 4/cut resistance: 5)

All levels only apply to the coated areas of the glove.

**EC notified body** Centexbel Gent  
Technologiepark 7 · BE - 9052 Zwijnaarde (Gent), Belgium  
No.: 0493

**Cleaning** Cleaning only possible when not working with aggressive chemicals. Carefully rinse gloves under lukewarm running water.

**Storage** Store in a dark, dry place.

**Handling** Thoroughly check before use for damage. Defective gloves should not be used. All technical data refers to the state of the gloves at delivery, unused, not stretched and at ambient temperature (EN 374). Gloves must be disposed of when the permeation time expires.

After contamination, a change of performance cannot be excluded.  
We are not aware of any substances in this product that could cause an allergic reaction.

**Disposal** The gloves should be disposed of properly as household waste. If they come into contact with chemicals, please consult the chemical manufacturer's waste disposal guidelines.

**Warning** Gloves should not be worn where there is a risk of being caught in moving machinery parts.